

### PARAMETERS

Impedance	4 ohms
Re	3.5 ohms
Le	0.13 mH @ 1 kHz
Fs	450 Hz
Qms	N/A
Qes	N/A
Qts	N/A
Mms	N/A
Cms	N/A
Sd	N/A
Vd	N/A
BL	N/A
Vas	N/A
Xmax	N/A
VC Diameter	19 mm
SPL	N/A
RMS Power Handling	5 watts
Usable Frequency Range (Hz)	N/A


### FEATURES

- Rare-earth neodymium motor and a proprietary vented voice coil
- 4 ohms impedance for use with small, Class D amplifiers
- Four arms provide extra support improving linearity
- Turns any flat, rigid surface into a speaker

### APPLICATIONS


- Invisible home theater and multi-room audio
- Electronic gaming machines
- Advertising signage
- Point-of-purchase displays
- Multimedia exhibits
- Commercial distributed audio
- Kiosks
- Automotive audio
- Bathroom tubs and showers

### IMPEDANCE/PHASE



Measurement taken with transducer uncoupled facing upward.

### FREQUENCY RESPONSE



OmniMic

1/3<sup>rd</sup> octave smoothing - measurement taken with transducer adhered off-center on a 12" x 12" x 1/2" foam core board in an infinite baffle setup.

Note: This information is for comparison purposes only, the actual frequency response will depend on many factors of which the diaphragm being the greatest contributor.